



CUSHMAN®



HAULER™ 4X4

BUILT FOR WHERE THE WORK TAKES YOU.

The Cushman Hauler 4x4 is equipped with a 22-hp, 1,007cc 3-cylinder diesel engine, user-selectable 4WD, four-wheel independent suspension, and a large cargo bed. Offered in two-passenger or four-passenger models, this powerhouse is designed to handle the heaviest materials and equipment, and toughest terrain.

LET'S WORK.®

DIESEL

22HP
DIESEL

1300LB
MAX TOW

25MPH
MAX SPEED



2-PASSENGER



4-PASSENGER

CUSHMAN[®] HAULER™ 4X4 DIESEL



STANDARD BRUSH GUARD



OPTIONAL WORK LIGHTS

STANDARD THREE-POINT SEATBELT



4-WHEEL INDEPENDENT SUSPENSION

OPTIONS & ACCESSORIES

- Strobe Light
- Electric or Hydraulic Bed
- Work Lights
- Hard Cab
- Bed Liner
- Turf or Mud Tires
- Skid Plate
- Rear Screen
- Fog Light
- Side Mirrors

BODY & CHASSIS	4X4 DIESEL	4X4 DIESEL CREW
FRAME	Welded steel with powder-coat protection	Welded steel with powder-coat protection
BODY & FINISH	Injection Molded Body	Injection Molded Body
STANDARD COLOR	Patriot Blue	Patriot Blue
DIMENSIONS		
OVERALL LENGTH	114.4 in (290.5 cm)	146.7 in (372.5 cm)
OVERALL WIDTH	60.7 in (123 cm)	60.7 in (123 cm)
OVERALL HEIGHT	76.4 in (194.1 cm)	76.4 in (194.1 cm)
WHEEL BASE	76.4 in (194.1cm)	108.7 in (276.1 cm)
FRONT WHEEL TRACK	49.7 in (126.2 cm)	49.7 in (126.2 cm)
REAR WHEEL TRACK	49.8 in (126.4 cm)	49.8 in (126.4 cm)
GROUND CLEARANCE	12.0 in (30.5 cm)	12.0 in (30.5 cm)
CARGO BOX WIDTH (INSIDE)	56.2 in (142.7 cm)	56.2 in (142.7 cm)
CARGO BOX LENGTH (INSIDE)	38.5 in (97.8 cm)	38.5 in (97.8 cm)
CARGO BOX DEPTH (INSIDE)	11.5 in (29.2 cm)	11.5 in (29.2 cm)
POWER		
POWER SOURCE	3 Cylinders 61.5 cu in (1,007 cc)	3 Cylinders 61.5 cu in (1,007 cc)
VALVE TRAIN	OHV	OHV
HORSEPOWER (KW)	22 hp (16.4 kW)	22 hp (16.4 kW)
ELECTRICAL SYSTEM	Starter / Alternator	Starter / Alternator
BATTERY (QTY/TYP)	One, 12 Volt (690 CCA @ 0° F)	One, 12 Volt (690 CCA @ 0° F)
KEY OR PEDAL START	Key	Key
AIR CLEANER	Dry-Cyclone Type	Dry-Cyclone Type
LUBRICATION	Pressurized	Pressurized
OIL FILTER	Spin-On	Spin-On
COOLING SYSTEM	Liquid Cooled	Liquid Cooled
FUEL CAPACITY	7.4 Gallon (28.0 L) tank	7.4 Gallon (28.0 L) tank
DRIVETRAIN	Belt, Continuously Variable Transmission (CVT)	Belt, Continuously Variable Transmission (CVT)
TRANSAXLE	Differential Lock (Limited Slip Device)	Differential Lock (Limited Slip Device)
GEAR SELECTION	Forward H-Forward L- Neutral-Reverse	Forward H-Forward L- Neutral-Reverse
REAR AXLE RATIO	20:1 (Low), 13.5:1	20:1 (Low), 13.5:1
PERFORMANCE		
SEATING CAPACITY	2 Person, Bench	4 Person, Bench
CURB WEIGHT	1731 lb (785kg)	1852 lb (840 kg)
DRY WEIGHT	658 lb (298kg)	861 lb (391 kg)
BED LOAD CAPACITY	1102 lb (500 kg)	660 lb (300 kg)
VEHICLE LOAD CAPACITY	1600 lb (726 kg)	1325 lb (600 kg)
OUTSIDE CLEARANCE CIRCLE	26 ft (7.9 m)	35.4 ft (10.7 m)
SPEED	25 mph (40.2 kph)	25 mph (40.2 kph)
STEERING & SUSPENSION		
STEERING	Self-compensating Rack and Pinion	
FRONT/REAR SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum	
PARKING BRAKE	Self-compensating, Single Point Engagement	
FRONT/REAR TIRES	All-Terrain 25 x 10 - 12 in	